



EFG014026

EFG Izi Light

EFG Izi Light is a table range with adjustable T-foot and rectangular legs. The placement of the thickest part of the leg is upwards. The table has metal frame and is equipped with motor-driven height adjustment.

Product info

- With EFG Izi Light workstations you have the possibility to combine table tops and frames within the limits that design and standard allows.
- EFG Izi Light has a large number of table tops.
- Table tops with straight edges: 22 mm core of chip board with 0.6 mm veneer in beech (R5), ash white 2% (A2) and Birch (B5). Table tops in MFC (MB, MR, ME, MV, M6 and MA), HPL (HV) or linoleum (D4) have a 22 mm core of chip board and straight edges.
- Motor-driven height adjustment, two strokes: 470 or 600 mm. 700-1170 mm or 650-1250 mm, one motor per table.
- Metal frame with rectangular legs with the placement of the thickest part upwards and T-foot. Black (B=RAL 9005), silver (S=RAL 9006), White (W=RAL 9016).
- The frame has beams in the lengths: 850, 950, 1100, 1300, 1450 and 1600 mm, which is suitable for table tops from 1000 to 1800 mm.
- Maximum loading: 80 kg, spread over the table top.
- Assembling: Frame is fixed directly to the table top with enclosed screws.
- Accessories: Desk screens, modesty panels, cable management, CPU-holder and wall mount for flat screens.
- Guarantee: Five years liability for defects resulting from faulty design, materials or workmanship.
- Complies with established criteria for furniture eco-labelling. Minor deviations may occur.
- Tested according to: EN 527-1, EN 527-2, EN 527-3 and fulfill ISO 2016:2007 pkt 6.6. The tables are CE-marked and fulfill AFS2008:3 and AFS2009:5. EFG Izi Light with stroke 470 mm are not within the frame of minimum and maximum height according to EN 527-1.

TECHNICAL INFO:

- Power supply: 240 V.
- Speed, 45 kg: 22 mm/s.
- Stroke 470 och 600 mm.
- Maximum load: 80 kg (incl table top 25 kg)
- Overheating protection: 1 min operation, 9 min rest.
- Sound 52 dB
- Consumption in standby: 0,50 W (two legs)
- Temperature in the surroundings during operation: +5 till +40° C

EFG014034



EFG Izi Light, LO

EFG014035



EFG Izi Light, HI

EFG014038



EFG Izi Light height adjustment